

Exposure Scenario provided in accordance with EU Directive 2004/37/EC, Regulation (EC) No 1907/2006 Annex I and the terms of the REACH authorisation No. REACH/19/29/0

## 1. TITLE SECTION

<b>Substance</b>	<b>Chromium trioxide (CAS number 1333-82-0, EC number 215-607-8)</b>
<b>ES/use name</b>	<p>Use at industrial site: Chemical conversion and slurry coating applications by the aerospace sector<sup>1</sup>, where any of the following key functionalities or properties is necessary for the intended use: corrosion resistance, active corrosion inhibition, adhesion promotion and reproducibility (for chemical conversion coating), corrosion protection, heat resilience, hot corrosion resistance, resistance to humidity and hot water, thermal shock resistance, adhesion and flexibility (for slurry coating)</p> <p>Chromium trioxide may only be used for chemical conversion and slurry coating applications by the aerospace sector.</p> <p><u>Important note:</u> The authorisation for the use of chromium trioxide is <u>not</u> granted for chemical conversion and slurry coating applications by the aerospace sector where none of the key functionalities listed in the use is necessary for the intended use.</p>

### 1.1. Scope

#### ENVIRONMENT (Environment Contributing Scenario – ECS)

ECS 1: Use of chromium trioxide for chemical conversion and slurry coating applications by aerospace companies and their suppliers.	ERC 6b
-------------------------------------------------------------------------------------------------------------------------------------	--------

#### WORKER (Worker Contributing Scenario – WCS)

WCS 1: Delivery and storage of raw material	PROC 1
WCS 2: Decanting – liquids	PROC 8b
WCS 3: Mixing – liquids	PROC 5
WCS 4: Re-filling of baths	PROC 8b
WCS 5: Surface treatment by immersion/dipping	PROC 13
WCS 6: Substance preparation and surface treatment by spraying in paint booth	PROC 8b, 7
WCS 7: Surface treatment by brushing/or pen-stick use (small areas parts)	PROC 10
WCS 8: Maintenance of equipment	PROC 8a
WCS 9: Infrequent maintenance activities	PROC 8a
WCS 10: Sampling	PROC 8b
WCS 11: Machining operations on small to medium sized parts containing Cr(VI) on an extracted bench/extraction booth including cleaning	PROC 21, 24
WCS 12: Machining operations in large work areas on parts containing Cr(VI) including cleaning	PROC 21, 24
WCS 13: Machining operations on parts containing Cr(VI) in small work areas including cleaning	PROC 21, 24
WCS 14: Storage of articles	PROC 1
WCS 15: Waste management	PROC 8b
WCS 16: End of Life	PROC 8b

<sup>1</sup> Aerospace sector includes companies principally engaged in carrying out the design, development, manufacture, maintenance, modification, overhaul, repair, or support of civil or military aerospace and defence equipment, systems, or structures, plus any derivative uses.

This ES includes relevant information provided in the Wesco Aircraft EMEA Chemical Safety Report (CSR) for Chromium trioxide (see [AFA No. 0096-01](#)), in accordance with ECHA's illustrative example of an exposure scenario, and follows ECHA's guidance on extracting the relevant information from the comprehensive exposure scenarios in the CSR. This ES includes (is limited to):

- Chemical conversion coating (CCC)<sup>2</sup>,
- Slurry coatings including sacrificial coatings<sup>3</sup> and diffusion coatings and paints<sup>4</sup> for corrosion protection.

## 1.2. Explanation on the approach taken for the ES

All worker exposure estimates are given in terms of Cr(VI) and are expressed as 8 hour Time Weighted Average (TWA).

The frequency of a specific activity in the worker sub-scenarios is expressed as daily activity unless otherwise stated. *As long-term exposure is the relevant period for long-term health effects, the duration of exposure per day as set out in the ES is expressed as average duration per day over a longer period (e.g. 2 hours each day are equal to 4 hours every second day). Therefore, the duration of exposure per day is not the same as the maximum allowed duration in any one day.*

Occupational exposure estimates are based on measured data and/or on modelled data, using the exposure model 'Advanced REACH Tool 1.5' or 'ART'<sup>5</sup>. ART is a second-tier model calibrated to assess exposure to inhalable dust, vapours, and mists; this Exposure Scenario is within the scope of ART. Additional parameters used for the purpose of modelling are provided in the CSR for the relevant worker contributing scenarios (WCS).

Where the sample size and sampling strategy is adequate (i.e. personal sampling data), the risk characterisation relies on the measured exposure values. The results of exposure modelling were used for the risk characterisation when adequate measurement data were not available.

## 2. CONDITIONS OF USE AFFECTING EXPOSURE

This section includes the Operational Conditions (OCs) and Risk Management Measures (RMMs) for each contributing scenario.

### 2.1. ENVIRONMENT CONTRIBUTING SCENARIO: Use of chromium trioxide for chemical conversion and slurry coating applications by aerospace companies and their suppliers (ECS 1) (ERC 6b)

<i>Amount used, frequency and duration of use (or from service life)</i>	
▪ Daily use at site:	<= 0.0002 tonnes/day [as Cr(VI)]
▪ Annual use at a site:	<= 0.05 tonnes/year [as Cr(VI)]
▪ Percentage of tonnage used at regional scale:	= 33 %
<b>Technical and organisational conditions and measures</b>	
<ul style="list-style-type: none"> <li>▪ Air emission abatement: At least 99% efficiency. For operations where exposure potential is low [i.e. operations are infrequent using only small quantities of Cr(VI)] air emission abatement may not be necessary.</li> <li>▪ Negligible discharge of Cr(VI) in wastewater from the site</li> </ul>	

<sup>2</sup> CCC is a chemical process applied to a substrate producing a surface layer containing a compound of the substrate metal and other chemical species from the process solution.

<sup>3</sup> Sacrificial coatings have a lower electrode potential than the substrate to be protected.

<sup>4</sup> The diffusion coating / paint process is based on the coating material diffusing into the substrate at high temperatures.

<sup>5</sup> The use of ART for workers exposure assessment under REACH is described in ECHA's updated Guidance on Information Requirements and chemical safety assessment R.14, Vers. 2, May 2010. Background information for ART are provided in: Fransman W., Cherrie J., van Tongeren M., Schneider T., Tischer M., Schinkel J., Marquart H., Warren, N.D., Spankie S., Kromhout H., Tielemans E. Development of a mechanistic model for the Advanced REACH Tool (ART). Version 1.5, January 2013.

- All solid and any liquid waste is collected and either the collected waste is directly forwarded to an external waste management company, or Cr(VI) in wastewater is reduced to Cr(III) on-site, or treated by vacuum evaporation. The treated wastewater is discharged to municipal sewage system. Any solid or slurry waste is either recycled or forwarded to an external waste management company (licenced contractor) for disposal as hazardous waste

**Conditions and measures related to sewage treatment plant**

- Not applicable – negligible discharge of Cr(VI) in wastewater from the site

**Conditions and measures related to treatment of waste (including article waste)**

- Collection of all solid and liquid waste, elimination of Cr(VI) from waste water, reuse disposal as hazardous waste by an external waste management company (licenced contractor)

**Other conditions affecting environmental exposure**

- When needed, exhaust air from LEV is passed through dry filters and/or wet scrubbers according to best available technique (see air emission abatement above).

**2.1.1. Specific Conditions of REACH authorisation [C\(2019\) 7448](#) (Article 2, points 10(b), 11, 13, 14 and 15)**

- Implement at least annual monitoring programmes for chromium (VI) emissions to wastewater and air from local exhaust ventilation. Those programmes shall be based on relevant standard methodologies or protocols and be representative of the operational conditions and risk management measures (such as wastewater treatment systems, gaseous emission abatement techniques) used at the individual sites where measurements are carried out.
- The information gathered via the measurements and related contextual information shall be used by the authorisation holder and by its downstream users to regularly review the effectiveness of the risk management measures and operational conditions in place and to introduce measures to further reduce exposure and emissions.
- The results of those measurements as well as of any action taken following the review shall be documented and be made available by the authorisation holder and their downstream users, upon request, to the competent authorities of the Member State where the authorised uses take place.
- The downstream users shall make available to the Agency the information from the monitoring programme, including the contextual information associated to each set of measurements, for the first time by 24 October 2020, for transmission to the authorisation holder for the purpose of validating the exposure scenarios and afterwards for the preparation of the review report according to Article 61(1) of Regulation (EC) No 1907/2006. That information shall also be maintained and be made available by the authorisation holder and downstream users, upon request, to the competent authority of the Member State where the authorised use takes place.
- Continuation of monitoring requirements
  - Downstream users may reduce the frequency of measurements once they can clearly demonstrate to the competent authority of the Member State where the use takes place that exposure to humans and releases to the environment have been reduced to as low a level as technically and practically possible and that the risk management measures and operational conditions correspond to the exposure scenarios and function appropriately.
  - Where the frequency of the monitoring programme has been reduced, any subsequent changes to the operational conditions or risk management measures that may affect the exposure at the site where the use takes place shall be documented. The authorisation holder and its downstream users shall assess the impact of such changes by monitoring, to demonstrate that exposure of workers and emissions to the environment continue to be reduced to as low a level as technically and practically possible.

**2.2. WORKER CONTRIBUTING SCENARIOS 1 - 16**

<b>WCS 1: Delivery and Storage of raw material (PROC 1) in sealed containers</b>	
<b>Product (Article) characteristics</b>	
▪ Substance type	Substance as such/in a mixture
▪ Concentration of Cr(VI)	< 25%
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 1 hour
▪ Frequency of activity	infrequent
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Basic general ventilation (1-3 air changes per hour)
▪ Containment	Closed system (minimal contact during routine operations)
▪ Local exhaust ventilation	No localized controls
▪ Occupational Health and Safety Management System	Advanced <sup>6</sup>
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ PPE	Not required
<b>Other conditions affecting workers exposure</b>	
▪ Place of use	Indoor
▪ Temperature	Room temperature
<b>Exposure Concentration</b>	
Inhalation, local, long-term	<b>0 µg/m<sup>3</sup></b> – no potential for worker exposure

<b>WCS 2: Decanting of liquids (PROC 8b) (e.g. before re-filling of baths or for further mixing)</b>	
<b>Product (Article) characteristics</b>	
▪ Substance product type	Liquid
▪ Concentration of Cr(VI) in mixture	< 25%
▪ Vapour pressure of substance	< 0.01 Pa
▪ Viscosity	Low
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 15 min
▪ Frequency of activity	1 time/week (reduction factor of 0.2 applied)
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	No localized controls

<sup>6</sup> Such systems are consistent with the duty of care set out through general Health and Safety at Work legislation, as well as via more specific legislation, such as the Carcinogens Directive (2004/37/EC) and the Chemical Agents at Work Directive (98/24/EC) and include, for example: areas using Cr(VI) are restricted to essential workers with appropriate PPE; workers are informed of temporary, planned higher exposure and how to minimise exposure; appropriate hygienic procedures are in place; appropriate training is provided on potential risks to health, exposure prevention, hygiene requirements, PPE, etc.; appropriate warning and hazard labelling is provided; workers are informed on abnormal exposures as quickly as possible, etc.

<b>WCS 2: Decanting of liquids (PROC 8b) (e.g. before re-filling of baths or for further mixing)</b>	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
<ul style="list-style-type: none"> <li>PPE</li> </ul>	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
<ul style="list-style-type: none"> <li>Process temperature</li> </ul>	Room temperature
<ul style="list-style-type: none"> <li>Work area</li> </ul>	Indoors
<ul style="list-style-type: none"> <li>Room size</li> </ul>	Any size workroom
<ul style="list-style-type: none"> <li>Process fully enclosed?</li> </ul>	No
<ul style="list-style-type: none"> <li>Effective housekeeping practices in place?</li> </ul>	Yes
<b>Exposure Concentration</b>	
Inhalation, local, long-term	<b>1.3 µg/m<sup>3</sup></b> (modelled with ART 1.5)
Inhalation, local, long-term (adjusted for frequency)	<b>0.26 µg/m<sup>3</sup></b> (modelled with ART 1.5)

<b>WCS 3: Mixing – liquids (PROC 5) (e.g. before re-filling of baths)</b>	
<b>Product (article) characteristics</b>	
<ul style="list-style-type: none"> <li>Substance product type</li> </ul>	Liquid
<ul style="list-style-type: none"> <li>Concentration of Cr(VI) in mixture</li> </ul>	< 25%
<ul style="list-style-type: none"> <li>Vapour pressure of substance</li> </ul>	< 0.01 Pa
<ul style="list-style-type: none"> <li>Viscosity</li> </ul>	Low
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
<ul style="list-style-type: none"> <li>Duration of activity</li> </ul>	< 30 min
<ul style="list-style-type: none"> <li>Frequency of activity</li> </ul>	1 time/week (reduction factor of 0.2 applied)
<b>Technical and organisational conditions and measures</b>	
<ul style="list-style-type: none"> <li>General ventilation</li> </ul>	Good natural ventilation (0 – 2 air changes per hour)
<ul style="list-style-type: none"> <li>Local exhaust ventilation</li> </ul>	No localized controls
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
<ul style="list-style-type: none"> <li>PPE</li> </ul>	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
<ul style="list-style-type: none"> <li>Process temperature</li> </ul>	Room temperature
<ul style="list-style-type: none"> <li>Process fully enclosed?</li> </ul>	No
<ul style="list-style-type: none"> <li>Effective housekeeping practices in place?</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Work area</li> </ul>	Indoors
<ul style="list-style-type: none"> <li>Room size</li> </ul>	Any size workroom
<b>Exposure Concentration</b>	
Inhalation, local, long-term	<b>0.64 µg/m<sup>3</sup></b> (modelled with ART 1.5)
Inhalation, local, long-term (adjusted for frequency)	<b>0.13 µg/m<sup>3</sup></b> (modelled with ART 1.5)

<b>WCS 4: Re-filling of baths (PROC 8b)<sup>7</sup></b>	
<b>Product (article) characteristics</b>	
▪ Substance product type	Liquid
▪ Concentration of Cr(VI) in mixture	< 25%
▪ Vapour pressure of substance	< 0.01 Pa
▪ Viscosity	Low
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 10 min
▪ Frequency of activity	1 time/week (reduction factor of 0.2 applied)
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	Fixed capturing hood <sup>8</sup> (90.00 % reduction)
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Process temperature	Above room temperature
▪ Process fully enclosed?	No
▪ Effective housekeeping practices in place?	Yes
▪ Work area	Indoors
▪ Room size	Any size workroom
<b>Specific Condition(s) imposed by the granted authorisation</b>	
▪ Effective cleaning practices shall be implemented to prevent surface contamination around treatment baths and other equipment.	
<b>Exposure Concentration</b>	
Inhalation, local, long-term	<b>0.95 µg/m<sup>3</sup></b> (modelled with ART 1.5)
Inhalation, local, long-term (adjusted for frequency)	<b>0.19 µg/m<sup>3</sup></b> (modelled with ART 1.5)

<b>WCS 5: Surface treatment by immersion/dipping (PROC 13)<sup>9</sup> (e.g. within one or more tanks in a surface treatment process)</b>	
<b>Product (article) characteristics</b>	
▪ Substance product type	Liquid
▪ Concentration of Cr(VI) in mixture	Small (1 - 5%)
▪ Vapour pressure of substance	< 0.01 Pa
▪ Viscosity	Low
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 1 h

<sup>7</sup> This scenario covers as worst-case similar activities in which a complete emptying and re-filling of a bath is conducted (without LEV).

<sup>8</sup> Or equivalent LEV to achieve the specified percent reduction

<sup>9</sup> Cleaning of equipment is not a separate task but conducted by those employees working in the bath area as part of their normal working procedure.

<b>WCS 5: Surface treatment by immersion/dipping (PROC 13)<sup>9</sup> (e.g. within one or more tanks in a surface treatment process)</b>	
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	Fixed capturing hood <sup>8</sup> (90.00 % reduction)
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Process temperature	Above room temperature
▪ Process fully enclosed?	No
▪ Effective housekeeping practices in place?	Yes
▪ Work area	Indoors
▪ Room size	Any size workroom
<b>Specific Condition(s) imposed by the granted authorisation</b>	
Effective cleaning practices shall be implemented to prevent surface contamination around treatment baths and other equipment.	
<b>Exposure Concentration</b>	
Inhalation, local, long-term	<b>0.023 µg/m<sup>3</sup></b> (modelled with ART 1.5)

<b>WCS 6: Substance preparation and surface treatment by spraying in paint booth (PROC 8b, 7)</b>	
<b>Conditions by Sub-task</b>	
<b>Sub-task 1: Mix Coating prior to filling of paint gun</b>	
<b>Product (article) characteristics</b>	
▪ Substance type	Substance in a mixture
▪ Concentration of Cr(VI)	< 1-5 %
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 5 min
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	Yes (90% reduction)
▪ Occupational Health and Safety Management System	Advanced <sup>6</sup>
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Place of use	Indoor
▪ Process temperature	Room temperature

<b>Sub-task 2: Filling of Paint Gun</b>	
<b>Product (article) characteristics</b>	
▪ Substance type	Substance in a mixture
▪ Concentration of Cr(VI)	< 1-5 %
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 5 min
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	No localized controls
▪ Occupational Health and Safety Management System	Advanced <sup>6</sup>
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ Respiratory Protection	Yes, at least half-face mask with P3 filter
▪ Other PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Place of use	Indoor
▪ Process temperature	Room temperature

<b>Sub-task 3: Masking and Degreasing, including sandblasting to remove existing surface coating</b>	
<b>Product (article) characteristics</b>	
▪ Substance type	Substance in a mixture
▪ Concentration of Cr(VI)	< 1-5 %
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 5 min
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	No localized controls
▪ Occupational Health and Safety Management System	Advanced <sup>6</sup>
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ Respiratory Protection	Yes, at least half-face mask with P3 filter
▪ Other PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Place of use	Indoor
▪ Process temperature	Room temperature



<b>Sub-task 4: Spraying in Paint Booth</b>	
<b>Product (article) characteristics</b>	
▪ Substance type	Substance in a mixture
▪ Concentration of Cr(VI)	< 1-5 %
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 30 min
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	Yes (e.g. down-flow spray room/paint booth) (80% reduction)
▪ Occupational Health and Safety Management System	Advanced <sup>6</sup>
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ Respiratory Protection	yes, at least half-face mask with P3 filter
▪ Other PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Place of use	Spray room/Paint booth
▪ Process temperature	Room temperature

<b>Sub-task 5: Article Drying</b>	
<b>Product (article) characteristics</b>	
▪ Substance type	Substance in a mixture
▪ Concentration of Cr(VI)	residual
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 15 min
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	No localized controls
▪ Occupational Health and Safety Management System	Advanced <sup>6</sup>
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ Respiratory Protection	Yes, at least half-face mask with P3 filter
▪ Other PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Place of use	Indoor
▪ Process temperature	High

<b>Sub-task 6: Article Curing</b>	
<b>Product (article) characteristics</b>	
▪ Substance type	Substance in a mixture

<b>Sub-task 6: Article Curing</b>	
▪ Concentration of Cr(VI)	residual
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 180 min
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation
▪ Local exhaust ventilation	No localized controls
▪ Occupational Health and Safety Management System	Advanced <sup>6</sup>
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Place of use	Indoor
▪ Process temperature	High

<b>Sub-task 7: Tools Cleaning (spray cabin/booth)</b>	
<b>Product (article) characteristics</b>	
▪ Substance type	Substance in a mixture
▪ Concentration of Cr(VI)	< 1-5 %
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 15 min
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	Yes (e.g. down-flow spray room/paint booth) (80% reduction)
▪ Occupational Health and Safety Management System	Advanced <sup>6</sup>
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ Respiratory Protection	Yes, at least half-face mask with P3 filter
▪ Other PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Place of use	Spray room/Paint booth
▪ Process temperature	Room temperature

<b>Exposure Concentrations for Worker contributing scenario 6: Substance preparation and surface treatment by spraying in paint booth (PROC 8b, 7)</b>	
Inhalation, local, long-term (90 <sup>th</sup> Percentile)	<b>11.06 µg/m<sup>3</sup></b> (measured)
Inhalation, local, long-term (adjusted for RPE <sup>10</sup> )	<b>0.27 µg/m<sup>3</sup></b> (measured)

<sup>10</sup> Based on aggregated measurement data individually adjusted for specific APF [range 10 – 1000]

<b>WCS 7: Surface treatment by brushing or pen-stick use (small sized areas) (PROC 10) (e.g. on surfaces with or without electrical current)</b>	
<b>Product (article) characteristics</b>	
▪ Substance product type	Liquid
▪ Concentration of Cr(VI) in mixture	Small (1 - 5%)
▪ Vapour pressure of substance	< 0.01 Pa
▪ Viscosity	Low
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 60 min
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	No localized controls
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Process temperature	Room temperature
▪ Process fully enclosed?	No
▪ Effective housekeeping practices in place?	Yes
▪ Work area	Indoors
▪ Room size	Any size workroom
<b>Exposure Concentration</b>	
Inhalation, local, long-term	<b>0.23 µg/m<sup>3</sup></b> (modelled with ART 1.5)

<b>WCS 8: Maintenance of equipment (PROC 8a) (e.g. baths and related equipment)</b>	
<b>Product (article) characteristics</b>	
▪ Substance product type	Liquid
▪ Concentration of Cr(VI) in mixture	Small (1 - 5%)
▪ Vapour pressure of substance	< 0.01 Pa
▪ Viscosity	Low
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 60 min
▪ Frequency of activity	1 time/2 weeks (reduction factor of 0.1 applied)
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	No localized controls
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.

<b>WCS 8: Maintenance of equipment (PROC 8a) (e.g. baths and related equipment)</b>	
<b>Other conditions affecting worker exposure</b>	
▪ Process temperature	Room temperature
▪ Process fully enclosed?	No
▪ Effective housekeeping practices in place?	Yes
▪ Work area	Indoors
▪ Room size	Any size workroom
<b>Exposure Concentration</b>	
Inhalation, local, long-term	<b>0.023 µg/m<sup>3</sup></b> (modelled with ART 1.5)
Inhalation, local, long-term (adjusted for frequency):	<b>2.3E-03 µg/m<sup>3</sup></b> (modelled with ART 1.5)
<b>WCS 9: Infrequent maintenance activities (PROC 8a) (e.g. including exhaust systems, removal and replacement of filters, etc.)</b>	
<b>Product (article) characteristics</b>	
▪ Substance product type	Powders, granules or pelletised material
▪ Powder weight fraction [Cr(VI)]	Small (1 - 5%)
▪ Dustiness	Fine Dust
▪ Moisture content	Dry product (< 5 % moisture content)
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	240 min
▪ Frequency of activity	1 time/month (reduction factor of 0.05 applied)
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	No localized controls
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ Respiratory Protection:	Yes, at least half-mask with A2P3 filter
▪ Other PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Process fully enclosed?	No
▪ Effective housekeeping practices in place?	Yes
▪ Work area	Indoors
▪ Room size	Any size workroom
<b>Specific Condition(s) imposed by the granted authorisation</b>	
The area in which activities with solid chromates are conducted shall be restricted either physically by means of barriers or through strict procedure during the activity and for a specified time after the operation.	
Effective cleaning practices shall be implemented to prevent surface contamination where solid chromates are handled.	

**WCS 9: Infrequent maintenance activities (PROC 8a) (e.g. including exhaust systems, removal and replacement of filters, etc.)**

Exposure Concentration	
Inhalation, local, long-term	53.0 µg/m <sup>3</sup> (modelled with ART 1.5)
Inhalation, local, long-term (adjusted for frequency)	2.65 µg/m <sup>3</sup> (modelled with ART 1.5)
Inhalation, local, long-term (adjusted for frequency and RPE <sup>11</sup> )	0.088 µg/m <sup>3</sup> (modelled with ART 1.5)

**WCS 10: Sampling (PROC 8b)**

Product (article) characteristics	
▪ Substance product type	Liquid
▪ Concentration of Cr(VI) in mixture	Small (1 - 5%)
▪ Vapour pressure of substance	< 0.01 Pa
▪ Viscosity	Low
Amount used (or contained in articles), frequency and duration of use/exposure	
▪ Duration of activity	< 30 min
▪ Frequency of activity	1 time/week (reduction factor of 0.2 applied)
Technical and organisational conditions and measures	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	Fixed capturing hood <sup>8</sup> (90.00 % reduction)
Conditions and measures related to personal protection, hygiene and health evaluation	
▪ PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
Other conditions affecting workers exposure	
▪ Process temperature	Room temperature
▪ Process fully enclosed?	No
▪ Effective housekeeping practices in place?	Yes
▪ Work area	Indoors
▪ Room size	Any size workroom
Exposure Concentration	
Inhalation, local, long-term	0.011 µg/m <sup>3</sup> (modelled with ART 1.5)
Inhalation, local, long-term (adjusted for frequency)	2.2E-03 µg/m <sup>3</sup> (modelled with ART 1.5)

**WCS 11: Machining operations on small to medium sized parts containing Cr(VI) on an extracted bench/extraction booth including cleaning (PROC 21, 24)**

Product (article) characteristics	
▪ Substance product type	Solid object
▪ Solid weight fraction	< 0.1 % <sup>12</sup>

<sup>11</sup> A factor of 30 was applied, based on an APF 30 assigned for this RPE according to the German BG rule 190

<sup>12</sup> The Cr(VI) weight fraction of the part is assumed to be < 0.1 %. In case of lower or higher Cr(VI) content, estimated exposure would be reduced or increased in a linear way. If needed, OCs and RMMs could be adjusted for that different situation.

<b>WCS 11: Machining operations on small to medium sized parts containing Cr(VI) on an extracted bench/extraction booth including cleaning (PROC 21, 24)</b>	
▪ Moisture content	Dry product (<5 % moisture content)
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity:	< 60 min <sup>13</sup>
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	Fixed capturing hood /Vacuum cleaner <sup>8</sup> (HEPA filter with at least 99.00 % reduction)
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ Respiratory Protection	Yes, at least half mask with P3 filter  <i>(At least half mask with P3 filter is worn if workplace monitoring data do not confirm negligible exposure clearly below 1 µg/m<sup>3</sup> (e.g. &lt; 0.1 µg/m<sup>3</sup>)</i>
▪ PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Process fully enclosed?	No
▪ Effective housekeeping practices in place?	Yes
▪ Work area	Indoors
▪ Equipment level	Any size workroom
<b>Specific Condition(s) imposed by the granted authorisation</b>	
Effective cleaning practices shall be implemented to prevent surface contamination in the vicinity where machining activities take place.	
<b>Exposure Concentration</b>	
Inhalation, local, long-term	<b>0.38 µg/m<sup>3</sup></b> (modelled with ART 1.5)
Inhalation, local, long-term (adjusted for RPE <sup>11</sup> )	<b>0.013 µg/m<sup>3</sup></b> (modelled with ART 1.5)

<b>WCS 12: Machining operations in large work areas on parts containing Cr(VI) including cleaning (PROC 21, 24)</b>	
<b>Product (article) characteristics</b>	
▪ Substance product type	Solid object
▪ Solid weight fraction	< 0.1 % <sup>12</sup>
▪ Moisture content	Dry product (<5 % moisture content)
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 30 min <sup>13</sup>
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	10 air changes per hour (ACH)

<sup>13</sup> This scenario covers also machining operations with a longer duration of activity but with a higher level of respiratory protection, e.g. by using a full face mask with P3 filter (e.g. APF 400 according to the German BG rule 190).

<b>WCS 12: Machining operations in large work areas on parts containing Cr(VI) including cleaning (PROC 21, 24)</b>	
▪ Local exhaust ventilation	Wetting at the point of release/on-tool extraction <sup>8</sup> (90.00 % reduction)/ vacuum cleaning
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ Respiratory Protection	Yes, at least half mask with P3 filter  <i>(At least half mask with P3 filter is worn if workplace monitoring data do not confirm negligible exposure clearly below 1 µg/m<sup>3</sup> (e.g. &lt; 0.1 µg/m<sup>3</sup>)</i>
▪ PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Process fully enclosed?	No
▪ Effective housekeeping practices in place?	Yes
▪ Work area	Indoors
▪ Room size	Large workrooms only
<b>Specific Condition(s) imposed by the granted authorisation</b>	
Effective cleaning practices shall be implemented to prevent surface contamination in the vicinity where machining activities take place.	
<b>Exposure Concentration</b>	
Inhalation, local, long-term	<b>0.83 µg/m<sup>3</sup></b> (modelled with ART 1.5)
Inhalation, local, long-term (adjusted for RPE <sup>11</sup> ):	<b>0.028 µg/m<sup>3</sup></b> (modelled with ART 1.5)

<b>WCS 13: Machining operations on parts containing Cr(VI) in small work areas including cleaning (PROC 21, 24)</b>	
<b>Product (article) characteristics</b>	
▪ Substance product type	Solid object
▪ Solid weight fraction	< 0.1 % <sup>12</sup>
▪ Moisture content	Dry product (< 5 % moisture content)
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 30 min
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Local exhaust ventilation	No localized controls (See specific conditions below)
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ Respiratory Protection	Yes, Full face mask with P3 filter  <i>Full face mask with P3 filter is worn if workplace monitoring data do not confirm negligible exposure clearly below 1 µg/m<sup>3</sup> (e.g. &lt; 0.1 µg/m<sup>3</sup>)</i>

<b>WCS 13: Machining operations on parts containing Cr(VI) in small work areas including cleaning (PROC 21, 24)</b>	
▪ Other PPE	Protective clothing; chemical-resistant, impermeable gloves; goggles. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Process fully enclosed?	No
▪ Effective housekeeping practices in place?	Yes
▪ Work area	Indoors
▪ Room size	Small workrooms only
<b>Specific Condition(s) imposed by the granted authorisation</b>	
Mechanical ventilation shall be used for machining activities in small work areas, except in cases where mechanical ventilation would introduce risks or would otherwise not be technically and practically possible.	
Effective cleaning practices shall be implemented to prevent surface contamination in the vicinity where machining activities take place.	
<b>Exposure Concentration</b>	
Inhalation, local, long-term	<b>32 µg/m<sup>3</sup></b> (modelled with ART 1.5)
Inhalation, local, long-term (adjusted for RPE <sup>14</sup> ):	<b>0.08 µg/m<sup>3</sup></b> (modelled with ART 1.5)

<b>WCS 14: Storage of articles (PROC 1)</b>	
<b>Product (article) characteristics</b>	
▪ Concentration of substance Cr(VI) in article	Non detectable or very low
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 8 hours
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Basic general ventilation (1-3 air changes per hour)
▪ Local exhaust ventilation	No localized controls
▪ Occupational Health and Safety Management System	Advanced <sup>6</sup>
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ PPE	Not required
<b>Other conditions affecting workers exposure</b>	
▪ Place of use	Indoor/outdoors
▪ Process temperature (for solids)	Ambient
<b>Exposure Concentration</b>	
Inhalation, local, long-term	0 µg/m <sup>3</sup> – no potential for worker exposure

<b>WCS 15: Waste management (PROC 8b) (e.g. transfer of solid waste (e.g. empty containers, canisters, pencils, masking material, etc.) to the waste storage area)</b>	
<b>Product (article) characteristics</b>	
▪ Substance product type	Powders, granules or pelletised material
▪ Powder weight fraction [Cr(VI)]	Small (1 – 5%)

<sup>14</sup> A factor of 400 was applied, based on an APF 400 assigned for this RPE according to the German BG rule 190



<b>WCS 15: Waste management (PROC 8b) (e.g. transfer of solid waste (e.g. empty containers, canisters, pencils, masking material, etc.) to the waste storage area)</b>	
▪ Dustiness	Firm granules, flakes or pellets
▪ Moisture content	Dry product (< 5 % moisture content)
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
▪ Duration of activity	< 15 min
<b>Technical and organisational conditions and measures</b>	
▪ General ventilation	Good natural ventilation (0 – 2 air changes per hour)
▪ Primary	No localized controls
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
▪ PPE	PPE is not specified according to this Authorisation. Section 8 of the applicable SDS contains supplier advice to inform PPE selection for this task, which may include additional considerations.
<b>Other conditions affecting workers exposure</b>	
▪ Process fully enclosed?	No
▪ Effective housekeeping practices in place?	Yes
▪ Work area	Indoors
▪ Room size	Any size workroom
<b>Specific Condition(s) imposed by the granted authorisation</b>	
The area in which activities with solid chromates are conducted shall be restricted either physically by means of barriers or through strict procedure during the activity and for a specified time after the operation.	
Effective cleaning practices shall be implemented to prevent surface contamination where solid chromates are handled.	
<b>Exposure Concentration</b>	
Inhalation, local, long-term	<b>0.037 µg/m<sup>3</sup></b> (90th percentile value, modelled with ART 1.5)

### 2.2.1. Risk characterization related to combined exposure

Workers in the process of use of chromium trioxide for chemical conversion and slurry coating applications by aerospace companies and their suppliers could conduct some combinations of tasks (sub-scenarios). The core activities will be the sequential process steps of the application in baths and the slurry coating processes. A possible combination of sub-scenarios is the combination of WCS 2-5 and 10, activities in relation to the CCC application in baths. The combined exposure estimate (as the 90<sup>th</sup> percentile value of model-based exposure distribution) of these activities would be 0.60 µg/m<sup>3</sup>.

A further possible combination of activities would be the machining activities (WCS 11-13). The combined exposure estimate (as the 90<sup>th</sup> percentile value of model-based exposure distribution) of these activities would be 0.121 µg/m<sup>3</sup>.

### 2.2.2. Other Specific Conditions of REACH authorisation [C\(2019\) 7448](#) (Article 2, points 5, 9, 10(a), 11, 13, 14 and 15)

- Downstream users shall implement best practices to reduce workplace exposure to chromium trioxide and emissions to the environment to as low a level as technically and practically feasible, including the use of closed systems and automation, whenever possible. Where this is not possible, the downstream

users shall use local exhaust ventilation (LEV) systems that are appropriately designed, dimensioned, located and maintained to capture and remove chromium trioxide.

- LEV and personal respiratory equipment (RPE) shall be checked and tested periodically (including fit testing of RPE) and records of these periodical checks and tests shall be kept and made available for national competent authorities.
- Implement at least annual air monitoring programmes in accordance with Article 5(5)(e) of Directive 2004/37/EC. The first measurements shall be performed without delay and at the latest by 24 April 2020. Those programmes shall be based on relevant standard methodologies or protocols and be representative of:
  - the range of tasks undertaken where exposure to chromium is possible, including tasks involving process and maintenance workers;
  - the operational conditions and risk management measures typical for each of these tasks;
  - the number of workers potentially exposed
- The information gathered via the measurements and related contextual information shall be used by the authorisation holder and by its downstream users to regularly review the effectiveness of the risk management measures and operational conditions in place and to introduce measures to further reduce exposure and emissions.
- The results of those measurements as well as of any action taken following the review shall be documented and be made available by the authorisation holder and their downstream users, upon request, to the competent authorities of the Member State where the authorised uses take place.
- The downstream users shall make available to the Agency the information from the monitoring programme, including the contextual information associated to each set of measurements, for the first time by 24 October 2020, for transmission to the authorisation holder for the purpose of validating the exposure scenarios and afterwards for the preparation of the review report according to Article 61(1) of Regulation (EC) No 1907/2006. That information shall also be maintained and be made available by the authorisation holder and downstream users, upon request, to the competent authority of the Member State where the authorised use takes place.
- Continuation of monitoring requirements
  - Downstream users may reduce the frequency of measurements once they can clearly demonstrate to the competent authority of the Member State where the use takes place that exposure to humans and releases to the environment have been reduced to as low a level as technically and practically possible and that the risk management measures and operational conditions correspond to the exposure scenarios and function appropriately.
  - Where the frequency of the monitoring programme has been reduced, any subsequent changes to the operational conditions or risk management measures that may affect the exposure at the site where the use takes place shall be documented. The authorisation holder and its downstream users shall assess the impact of such changes by monitoring, to demonstrate that exposure of workers and emissions to the environment continue to be reduced to as low a level as technically and practically possible.

## 2.3. Exposure estimation and reference to its source

### 2.3.1. Environmental release and exposure

#### Local releases to the environment

Release	Release factor estimation method	Explanation / Justification
Air	Release factor	<b>Initial release factor:</b> 0.1% <b>Final release factor:</b> 0.001% <b>Local release rate:</b> 2E-06 kg/day

### Exposure and risks for the environment and man via the environment

Protection target	Exposure concentration	Risk characterisation
Freshwater	Not relevant	-
Sediment (freshwater)	Not relevant	-
Marine water	Not relevant	-
Sediment (marine water)	Not relevant	-
Predator (freshwater)	Not relevant	-
Predator (marine water)	Not relevant	-
Top predator (marine water)	Not relevant	-
Sewage treatment plant	Not relevant	-
Air	<b>Local PEC:</b> 3.808E-10 mg/m <sup>3</sup>	-
Agricultural soil	Not relevant	-
Predator (terrestrial)	Not relevant	-
Man via Environment – Inhalation	<b>Local PEC:</b> 3.808E-10 mg/m <sup>3</sup>	Based on the dose-response relationship derived by the RAC, considering a 70 year exposure time (24h/day, 7d/week), the following excess lifetime risk up to age 89 is derived he general population is derived based on the estimated exposure: 1.1E-05 per 1000 exposed
Man via Environment - Oral	Not relevant	-

### 2.3.2. Worker exposure

#### Exposure concentrations and risks for worker

Worker Contributing Scenario	Route of exposure and type of effects	Exposure Concentration	Risk Characterisation <sup>15</sup>
WCS 1: Delivery and storage of raw material	Inhalation, local, long-term (qualitative)	0 µg/m <sup>3</sup> – no worker exposure	Not applicable
WCS 2: Decanting – liquids	Inhalation, local, long-term, further adjusted for frequency (90 <sup>th</sup> percentile, ART 1.5)	0.26 µg/m <sup>3</sup>	1.04 per 1000 exposed workers
WCS 3: Mixing – liquids	Inhalation, local, long-term, further adjusted for frequency (90 <sup>th</sup> percentile, ART 1.5)	0.13 µg/m <sup>3</sup>	0.51 per 1000 exposed workers
WCS 4: Re-filling of baths	Inhalation, local, long-term, further adjusted for frequency (90 <sup>th</sup> percentile, ART 1.5)	0.19 µg/m <sup>3</sup>	0.76 per 1000 exposed workers
WCS 5: Surface treatment by immersion/dipping	Inhalation, local, long-term (90 <sup>th</sup> percentile, ART 1.5)	0.023 µg/m <sup>3</sup>	0.092 per 1000 exposed workers

<sup>15</sup> Based on the dose-response relationship for lung cancer mortality derived by the RAC, considering a 40-year working life (8h/day, 5d/week), the excess lifetime lung cancer mortality risk up to age 89 is derived based on the estimated exposure.

Worker Contributing Scenario	Route of exposure and type of effects	Exposure Concentration	Risk Characterisation <sup>15</sup>
WCS 6: Substance preparation and surface treatment by spraying in paint booth	Inhalation, local, long-term, further adjusted for RPE (90 <sup>th</sup> percentile, measurement data)	0.27 µg/m <sup>3</sup>	1.08 per 1000 exposed workers
WCS 7: Surface treatment by brushing/or pen-stick use (small areas parts)	Inhalation, local, long-term (90 <sup>th</sup> percentile, ART 1.5)	0.23 µg/m <sup>3</sup>	0.92 per 1000 exposed workers
WCS 8: Maintenance of equipment	Inhalation, local, long-term, further adjusted for frequency (90 <sup>th</sup> percentile, ART 1.5)	2.3E-3 µg/m <sup>3</sup>	9.2E-3 per 1000 exposed workers
WCS 9: Infrequent maintenance activities	Inhalation, local, long-term, further adjusted for frequency and RPE (90 <sup>th</sup> percentile, ART 1.5)	0.088 µg/m <sup>3</sup>	0.35 per 1000 exposed workers
WCS 10: Sampling	Inhalation, local, long-term, further adjusted for frequency (90 <sup>th</sup> percentile, ART 1.5)	2.2E-3 µg/m <sup>3</sup>	8.8E-3 per 1000 exposed workers
WCS 11: Machining operations on small to medium sized parts containing Cr(VI) on an extracted bench/extraction booth including cleaning	Inhalation, local, long-term, further adjusted for RPE (90 <sup>th</sup> percentile, ART 1.5)	0.013 µg/m <sup>3</sup>	0.05 per 1000 exposed workers
WCS 12: Machining operations in large work areas on parts containing Cr(VI) including cleaning	Inhalation, local, long-term, further adjusted for RPE (90 <sup>th</sup> percentile, ART 1.5)	0.028 µg/m <sup>3</sup>	0.11 per 1000 exposed workers
WCS 13: Machining operations on parts containing Cr(VI) in small work areas including cleaning	Inhalation, local, long-term, further adjusted for RPE (90 <sup>th</sup> percentile, ART 1.5)	0.08 µg/m <sup>3</sup>	0.32 per 1000 exposed workers
WCS 14: Storage of articles	Inhalation, local, long-term (qualitative)	0 µg/m <sup>3</sup> – no worker exposure	Not applicable
WCS 15: Waste management	Inhalation, local, long-term (90 <sup>th</sup> percentile, ART 1.5)	0.037 µg/m <sup>3</sup>	0.15 per 1000 exposed workers
WCS 16: End of Life	Not applicable	Not applicable	Not applicable